

SAMSON INDONESIA BOILER


SSBV-SERIES

SSBV SPECIFICATION

ITEMS		UNIT	SSBV-100	SSBV-200	SSBV-300	SSBV-500	SSBV-750	SSBV-1T	SSBV-1.5T	SSBV-2T
Equivalent evaporation		Kg/hr	100	200	300	500	750	1,000	1,500	2,000
Generated heating Value		Kcal/hr	53,900	107,800	161,700	269,500	404,250	539,000	808,900	1,078,000
Maximum pressure		Kgf/cm ²	7			10				
Boiler efficiency		%	87	87	87	85	85	85	85	85
Water quantity storage		Liter	52	94	126	189	272	328	440	527
Power Supply			50 Hz 3 Phase 220V / 380 V							
Control System			ON - OFF			HIGH - LOW - OFF				
Power Requirement		kW	1.9	1.9	1.9	2.5	2.5	3.3	6.2	6.2
Connection Size	Steam	A	25	25	25	32	32	40	65	65
	Fuel Inlet	A	10	10	10	10	10	10	10	10
	Feed Water	A	25	25	25	25	25	25	25	25
	Blowdown	A	25	25	25	25	25	25	25	25
	Safety Valve	A	15	25	25	25	25	32	32	40
	Chimney	mm	200	200	250	250	300	350	350	400
Dimension	Length	mm	1200	1200	1200	1400	2100	2100	2300	2300
	Width	mm	1300	1350	1350	1400	1850	1850	2000	2000
	Height	mm	1200	1400	1750	2300	2300	2500	2500	2500
Weight		Kg	550	620	770	1100	1400	2200	2720	3050

ABOVE VALUES ARE BASED ON : STEAM PRESSURE 5 BAR, FEED WATER TEMPERATURE 20 CELSIUS
 **ABOVE SPECIFICATION IS ABLE TO CHANGE WITHOUT PREVIOUS NOTICE

POWER UP YOUR INDUSTRY



FOR MORE INFORMATION
VISIT US AT :
SAMSONINDONESIABOILER.COM



CONTACT US :
PT SAMSON DJAWA PERKASA

+62 817-7753-77 / +62 215-688-369

SAMSONDJAWAPERKASA@YAHOO.COM
SIB.BOILER@GMAIL.COM

JL RAYA LEGOK NO.88, BABAKAN, KEC. LEGOK
TANGERANG, BANTEN 15820